

# InsuBuild 1175

High range, water reducing superplasticiser for producing free flowing concretes and promoting high early and ultimate strengths.

## DESCRIPTION OF PRODUCT

The basic components of InsuBuild 1175 are synthetic polymers, which allow mixing water to be reduced considerably and concrete strength to be enhanced significantly, particularly at early ages.

InsuBuild 1175 is a chloride-free product.

## ADVANTAGES

InsuBuild 1175 allows the production of very flowable concrete, with a low w/c ratio.

Concrete with InsuBuild 1175 shows strengths higher than concrete without admixture having the same workability.

The increase in strength, especially evident at early ages, remains at later ages, both in air cured and steam cured processes.

Initial and final sets do not change significantly with respect to concrete without admixture.

## PRIMARY USES

- Production of rheoplastic self-compacting concrete.
- Pre-cast concrete.
- Low w/c ratio concrete.
- In complicated formwork or with congested reinforcement.

## COMPATIBILITY

InsuBuild 1175 is compatible with all cements and most air-entraining agents meeting the ASTM standards. The addition of InsuBuild 1175 and InsuAir 111 (air-entraining agent) to concrete is recommended where it is required to withstand freezing and thawing cycles.

## PACKAGING

InsuBuild 1175 is available in 1000 ltr bulk

## TYPICAL PROPERTIES

Colour:	Dark brown liquid
Specific gravity:	(1.165 ± 0.01) at 25° C
Chloride content:	Nil to BS 5075
Nitrate content:	Nil
pH:	5-7
Freezing point:	0°C;
Flashpoint:	N/A

## STANDARDS

ASTM C- 494 Type A and F  
BS 5075 Part 1 and 3

## DOSAGE

InsuBuild 1175 is normally dispensed depending on the desired plasticizing or water reducing effect at a rate of 0.8% - 2.5% of cement weight. Dependent upon mix requirement, it is possible to use a higher dosage of InsuBuild 1175 without causing any adverse effects upon the concrete.

Please consult Insumat's Technical Services Department for further information.

## DISPENSING

InsuBuild 1175 is a ready-to-use liquid, which is dispensed into the concrete together with mixing water.

The plasticising effect, or water reduction, is higher if the admixture is added to the concrete after 50-70% of the mixing water has been added. The addition of InsuBuild 1175 to dry aggregate or cement is not recommended. Automatic dispensers are available in your local market.

## InsuBuild 1175

High range, water reducing superplasticiser for producing free flowing concretes and promoting high early and ultimate strengths.

### WORKABILITY

InsuBuild 1175 ensures that free flowing concrete remains workable in excess of 3 hours at +20°C. Workability loss is dependent on temperature, on the type of cement, the nature of aggregates, the method of transport and initial workability. It is strongly recommended that concrete should be properly cured particularly in hot and dry climates.

### STORAGE

InsuBuild 1175 must be stored where temperatures do not drop below +5°C. If product has frozen, thaw and agitate until completely reconstituted. Store under cover, out of direct sunlight and protect from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice, consult Insumat's Technical Services Department.

### SHELF LIFE

Up to 24 months if stored according to manufacturer's instructions in unopened containers.

### SAFETY PRECAUTIONS

InsuBuild 1175 is not a fire or health hazard. Spillages should be washed down immediately with cold water.

For further information, refer to the material safety data sheet.

### NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information, contact Insumat's representative.

Insumat reserves the right to have the true cause of any difficulty determined by accepted test methods.

### QUALITY STATEMENT

All products manufactured by Insumat Egypt, are manufactured to procedures certified to conform to the quality, environment, health & safety management systems described in the ISO 9001:2015, standard.

\* Properties listed are based on laboratory controlled tests.

Actual measured data may vary due to circumstances beyond Insumat's control.

Manufacturing Insulating Materials and Products Company

Founded by  
**Osman Ahmed Osman**  
1974

☎ 011 1974 1974  
📍 Plot 83 El Motawereen - El Sadat City - Menofia  
✉ info@insumat.com  
🌐 www.insumat.com